

## **Product Technical Information Sheet**

Wienerberger Code 12705312

**Production Plant** Péruwelz (Belgium)

Soft Mud Moulded Stock Manufacture

Configuration Frogged

Red Multi Colour

Creased Appearance

215 x 102.5 x 65 Work Size (mm)

680 No. Pack Quantity

Individual Dry Brick Weight (kg) 2.2



## Technical Properties to BS EN 771-1

Size Tolerance (Mean/Range) T1/R1

Gross Dry Density (kg/m³/Tolerance) 1650 (D1)

Compressive Strength (N/mm²) ≥12

Thermal Conductivity (W/(m·K))

P=90% 0.69  $\lambda_{10,dry,unit}$  value (EN 1745 tabulated: S1)

**Durability Designation** F2

Water Absorption (%) ≤14

Initial Rate of Water Absorption

(kg/(m<sup>2</sup>·min))

Min. 1.0 Max. 5.0

S2 **Active Soluble Salts** 

Reaction to Fire Class A1

## Issue Date: 29/09/2020

Technical data correct at time of issue. Individual dry brick weights can vary and are for guidance only. Any questions regarding this data should be referred to the Wienerberger Technical Department. Due to the limitations of screen and print colour representation of product images it is advised that brick samples are viewed prior to ordering.





1000+ products to choose from



Expert help and advice



Comprehensive Design Services



**Technical Support**